
提出日 特願2002-265360

[**Z** 2]

Toshiaki TSUDA et al. Q77365 ARC TUBE DISCHARGE BULB Filing date: September 8, 2003 Darryl Mexic 202-663-7909 2 of 8 Fig. 2



1231 Fig. 3

Inside Diameter	Uhole luminous Flux Evaluation			
発光管内径(mm)	全光束 (lm)	判定	7	
0.5	1200	×		
1.0	1630	×		
1.5	2030	. 0	1	
2.0	2390	0		
2.5	2730	0		

1241 Fig.4

Inside Diamet	er Whole Luminous Flux	Eva	Evaluation		
発光管長(mm)	全光束(lm)	判定]		
6.0	2600	0] ·		
8.0	2560	0]		
10.0	2410	0]		
12.0	2250	0			
14.0	2030	0] .		
16.0	1780	×	}		
18.0	1370	×]		

[图5]

Toshiaki TSUDA et al. Q77365 ARC TUBE DISCHARGE BULB Filing date: September 8, 2003 Darryl Mexic 202-663-7909 3 of 8

Thickness of Light Eniting Tube (mm)

Durability

1	
発光管肉厚(mm)	耐久性
0.15	点消灯にてクラック発生
0.20	点消灯にてクラック発生
0.25	OK
0.50	OK
0.70	OK
1.00	οκ
1.20	OK
1.40	点消灯にてクラック発生


Fig. 5

[图6] Outside Diameter ol (mm)

発光管外径 d	(mm)	1.5	2.0	2.5	3.0	3.5	4.0	4.5
length of	4.0	0.37 ×	0.50 ×	0.62 ×	0.75 ×	×	×·	×
light Emitting Tube L (mm)	6.0	0.25 ×	0.33 O	0.41 O	0.50 ×	0.58 ×	0.66 ×	0.75 × ,
発光管長し	8.0	0.18 ×	0.25 O	0.31 O	0.37 O	0.43 O	0.50 O	0.56 ×
(mm)	10.0	0.15 ×	0.20 O	0.25 O	0.30 O	0.35 O	0.40 O	0.45 ×
	12.0	×	0.16 ×	0.20 O	0.25 O	0.29 O	0.33 O	0.37 ×
	14.0	×	×	0.17 ×	0.21 ×	0.25 O	0.28 O	0.32 ×


Fig. 6


Toshiaki TSUDA et al. Q77365 ARC TUBE DISCHARGE BULB Filing date: September 8, 2003 Darryl Mexic 202-663-7909 4 of 8 36 37 38 15a 15b 22 32 30




図打 Fig. 11


Toshiaki TSUDA et al. Q77365 ARC TUBE DISCHARGE BULB Filing date: September 8, 2003 Darryl Mexic 202-663-7909 6 of 8








Toshiaki TSUDA et al. Q77365 ARC TUBE DISCHARGE BULB Filing date: September 8, 2003 Darryl Mexic 202-663-7909 7 of 8



[图15]


Fig. 15



理番号=F-ZI

[図16]

Toshiaki TSUDA et al. Q77365
ARC TUBE DISCHARGE BULB
Filing date: September 8, 2003
Darryl Mexic 202-663-7909
8 of 8



Proof - 2002/09/11